



## Key Feature

- 10-inch capacitive touch screen
- Publishes and displays the image on the screen with resolution: 600 × 1024p
- 2 × 2MP HD camera, ultra-wide angel lens
- Deep learning algorithm: Face anti-spoofing
- Unlocks door by face recognition
- Face capacity: 3000
- Noise suppression and echo cancellation
- Stand-alone operation: Card enrollment, and face adding locally
- Protection level: IP65

## Approval

CE-EMC	a. EN 55032:2015 b. EN 61000-3-2:2014 c. EN 61000-3-3:2013 d. EN 50130-4:2011 +A1:2014
CE-LVD	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
ROHS	2011/65/EU
REACH	Regulation (EC) No 1907/2006
WEEE	2012/19/EU

## Specification


System parameters	
Operation system	Embedded Linux operation system
Operation method	Capacitive touch screen
Display parameters	
Display screen	10-inch colorful LCD
Display resolution	600 × 1024
Video Parameters	
Camera	2 × 2 MP HD IR camera
Night vision	Low illumination, IR supplement lights
WDR	True WDR
Field of view	Horizontal: 108° , Vertical: 59° , Diagonal: 129°
Video Compression Standard	H.264
Stream	Main stream: 1080p@30fps,720p@30fps Sub stream: D1
Resolution	Main stream : 1920 × 1080p, 720p Sub stream : 704 × 576p
Video frame rate	50 Hz, 60 Hz
Audio parameters	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio intercom	Two-way audio
Audio compression standard	G.711 U
Audio compression Rate	64 Kbps
Audio quality	Noise suppression and echo cancellation
Network parameters	
Network interface	10/100/1000 Mbps self-adaptive Ethernet interface
Access control parameters	
Card type	Mifare card, 13.56 MHz
Card capacity	10000
Face capacity	3000
Fingerprint module	Optical fingerprint module, Max. 3000 fingerprints
Relay	2
Interfaces	
RS-485	1
USB interface	1
I/O input	3
I/O output	2
Debugging port	1
Network interface	2
Alarm parameters	

TAMPER switch	1
General	
Protective level	IP 65
Power supply	12 VDC, 2A to 3A
Power consumption	≤ 18 W
Working temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Working humidity	10% to 90%
Installation	Flush mounting

## Available Model


DS-KD9613-E6

## Appearance and Interfaces



No.	Description	No.	Description
1	Light	4	Screen
2	Camera	5	Card Reading Area
3	Microphone	6	TAMPER

**Dimension**



Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com